

Standard Size Schedule

PATIO DOORS, SIDELIGHTS & TOPLIGHTS

- Security & safety is assured with 5mm, toughened armourplate glass.
- Units comply with national building regulations parts "N" - glazing.
- Adjustable nylon rollers in stainless steel housing provide a smooth, quiet, maintenance free action.
- Serrated trip free threshold.
- Sliding doors with an extra track for fly screens are also available.
- All units are reversible.
- A range of sidelights and toplights give you multiple ventilation.



BRICKWORK UNIT	OPENING	1500	1800	2100	2400	3000	3000	
	SIZE	1490	1790	2090	2390	2990	2990	
2100	BRICKWORK UNIT	2090						
			SD 1521 OX	SD 1821 OX	SD 2121 OX	SD 2421 OX	SD 3021 OX	SD 3021 OXXO
		3600	4200	4800	6000			
		3590	4190	4790	5990			

2100	BRICKWORK UNIT	2090				
			SD 3621 OXXO	SD 4221 OXXO	SD 4821 OXXO	SD 6021 OXXO

SIDELIGHTS

A range of Sidelights with safety glass in lower panel is available to provide that valuable ventilation so often required by local building by-laws.





































600	900	600	900	EXAMPLE
				BRICKWORK OPENING 3000
SL 621	SL 921	SL 621F	SL 921F	

Due to a continuous policy of research, development & improvement we reserve the right to alter design and or specifications without prior notification.

Standard Size Schedule

ALUMINIUM PROJECTED OUT WINDOWS

- Complies with National Building Regulations Part "N" - glazing.
- Easy cleaning from inside on upper installations.
- Woolpile weatherseals provide a draught-free, quiet operating window.
- No fittings visible in closed position, except for an attractive handle.
- Finished in either bronze or natural anodized, or in a powder coated finish.
- Units available in left - or right hand.





























		600	900	1200	1500	1800	2400
		590	890	1190	1490	1790	2390
600	590	 PT 66	 PT 96	 PT 126	 PT 156	 PTT 186	 PTT 246
	900	 PT 69	 PT 99	 PT 129	 PT 159	 PTT 189	 PTT 249
1200	1190	 PT 612	 PT 912	 PTT 1212	 PTT 1512	 PTT 1812	 PTT 2412
	1500					 PDDT 1812	 PDDT 2412
1500	1490	 PTT 615	 PTT 915	 PTT 1215	 PTT 1515	 PTT 1815	 PTT 2415
	1800					 PDDT 1815	 PDDT 2415
1800	1790	 PTT 618	 PTT 918	 PTT 1218	 PTT 1518	 PTT 1818	 PTT 2418
						 PDDT 1818	 PDDT 2418

Due to a continuous policy of research, development & improvement we reserve the right to alter design and or specifications without prior notification.

Standard Size Schedule

ALUMINIUM SLIDING WINDOWS

- Complies with National Building Regulations Part "N" - glazing.
- Factory glazed with 4mm or 5mm clear float or laminated safety glass. Obscure glass can also be fitted on request.
- Unit fully reversible.
- Non-rusting maintenance free.
- Finished in either natural or bronze anodizing, or in a powder coated finish.

		1200	1500	1800	2100	2400	2700	3000
		1190	1490	1790	2090	2390	2690	2990
BRICKWORK OPENING	600							
	590	SW126	SW156	SW186	SW216	SW246	SW276	SW306
	900							
	890	SW129	SW159	SW189	SW219	SW249	SW279	SW309
1200								
1190	SW1212	SW1512	SW1812	SW2112	SW2412	SW2712	SW3012	
1500								
1490	SW1215	SW1515	SW1815	SW2115	SW2415	SW2715	SW3015	
UNIT SIZE								

Due to a continuous policy of research, development & improvement we reserve the right to alter design and or specifications without prior notification.

Standard Size Schedule


PALACE DOORS & SHOP FRONTS

ALL SHOP FRONTS & PALACE DOORS ARE PURPOSE MADE & CAN COMPLY WITH YOUR INDIVIDUAL NEEDS

- Strength - door manufactured with hollow extrusions.
- Safety - 6.5 mm laminated safety glass.
- Door fully reversible.
- Lock – lever –lockset or knobset
- Maintenance free.
- Versatile - commercial and residential application.
- Door can be coupled to our standard products.
- Door can be fitted with an electric lock, floor spring or overhead door closer.























SINGLE DOOR



DOUBLE DOOR

SIDE HUNG PROJECTING OUT WINDOWS

- Complies with National Building Regulations part "N" - glazing.
- Easy cleaning from inside on upper installations due to friction stays.
- Woolpile weatherseals provide a draught-free, quiet operating window.
- Finished in either bronze or natural anodizing or a powder coated finish.
- Units available in either left- or right hand.

		600	1200	1500	1800	2400
		590	1190	1490	1790	2390
BRICKWORK OPENING	900	 6S9	 12S9	 15S9	 18S9	 24S9
	1200	 6S12	 12S12	 15S12	 18S12	 24S12
	1500	 6S15	 12S15	 15S15	 18S15	 24S15
	1800	 6S18	 12S18	 15S18	 18S18	 24S18
UNIT SIZE		890	1190	1490	1790	

Due to a continuous policy of research, development & improvement we reserve the right to alter design and or specifications without prior notification.